ALTACHEM Ltd.

Industrial & Oilfield Chemicals



ACL-SC50

(Scale Control 50) PAGE 1 OF 2

SCALE CONTROL 50

SCALE INHIBITOR SUMMER VERSION

TECHNICALDATA

DESCRIPTION

This highly active phosphate ester acid is a powerful scale and rust inhibitor designed for oil and gas wells. Once introduced into the well, it removes and prevents scale build-up. Benefits include an increase in production, the reduction in plugging of wells, the reduced need for costly wire line service, and the elimination of deposits on screens and tubing.

DIRECTIONS

This product can be added at the well head directly and injected into the flow lines at required rates based on the fluid volumes and the severity of the problem.

PACKAGING AVAILABILITY:

This product is available in the following packaging options:

20L 205L 1000L

PHYSICAL PROPERTIES:

For an extensive list of physical properties, refer to the MSDS.

State Liquid Odour n/a Color Colourless n/a kg/L Density 2.5 - 3.5pН **Cloud Point** n/a **Cloud Point (1%)** n/a Foam (1%) n/a

 TF: 1-866-414-1445 www.altachem.net



ACL-SC50

(Scale Control 50) PAGE 2 OF 2

SCALE CONTROL 50

SCALE INHIBITOR SUMMER VERSION

TECHNICALDATA

GENERAL FIRST AID INFORMATION

IN CASE OF INHALATIO N

Remove victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel. Immediately transport victim to an emergency care facility.

IN CASE OF INGESTION

Rinse victim's mouth with water. DO NOT INDUCE VOMITING. Have victim drink 300 mL of water to dilute material in stomach. If milk is available, it may be given AFTER the water. Transport victim to an emergency facility..

IN CASE OF CONTACT WITH SKIN

In case of contact with skin, remove contaminated clothing and flush with water for at least 60 minutes. Do not interrupt flushing. Transport to an emergency facility.

IN CASE OF CONTACT WITH EYES

In case of contact with eyes, continuously flush eyes with plenty of water or neutral saline solution for at least 60 minutes. Transport to an emergency facility.

PERSONAL PROTECTIVE EQUIPMENT REQUIRED IF HANDLING DIRECTLY

Impermeable gloves
Chemical goggles or safety glasses
NIOSH approved
Rubber boots required
Impermeable coveralls required
Eye-wash station required

TDG:

Preparation of TDS

For further details on the source of this information, see MSDS.

ALTACHEM LTD. 5507-76th Ave. EDMONTON, AB. T6B 0A7 FAX: 780-414-1446

PH: 780-414-1445 www.altachem.ca

E-mail-altachem@gmail.com

TF: 1-866-414-1445 www.altachem.net